
G-F70ZK: MEDIUM AND HIGH PRECISION FIBER OPTIC GYROSCOPE






As a new type of all-solid state gyro, fiber optic gyroscope has the advantages of fast start, wide measurement range and high reliability. G-F70ZK uniaxial medium and high precision fiber optic gyroscope can be applied to the application requirements of high precision inertial navigation system, such as land positioning orientation, vehicle north finding instrument, airborne navigation posture and Marine gyro. The specification is only applicable to G-F70ZK type products, including performance indicators, technical conditions, external dimensions and installation and use. Among them, the technical conditions include the environmental range, electrical performance and physical characteristics of the product.

PRODUCT MAIN SPECIFICATION

G-F70ZK-A G-F70ZK-B 2h continuous testing, 10s Zero bias stability °/hr (1σ,10s) ≤0.03 <0.05 smooth results Zero bias repeatability $^{\circ}/hr$ (1 σ) ≤0.02 ≤0.02 6 test data calculation results Random walk coefficient $\sqrt[9]{hr}$ ≤0.005 ≤0.003 The Scale factor of Nonlinearity ≤10 ≤10 normal atmospheric temperature $ppm (1\sigma)$ The Scale factor of Repeatability ≤10 <20 normal atmospheric temperature ppm (1σ) Full-temperature scale factor ≤300 ≤200 -40°C∼+60°C repeatability $ppm (1\sigma)$ Dynamic range %s ±500 Magnetic field ≤0.02 sensitivity °/hr/Gs Working temperature $\,^{\circ}$ C $-40 \sim +70$ Storage temperature $\,^{\circ}\!\mathbb{C}$ -50~+70 Sweep frequency vibration has no Vibration conditions Hz $4.2q, 20\sim2000$ resonance

PRODUCT DIMENSION



SIZE: Φ70*29MM

PRODUCT APPLICATION

- Fiber optic gyroscope system
- Petroleum geological logging
- Underwater navigation
- North finding instrument
- Navigation GPS

- Marine survey
- Ship navigation attitude measurement
- Angle control of various construction machinery
- Stabilization platform equipment
- Unmanned aerial vehicles (UAV)
- Satellite solar antenna positioning